

MATERIAL SAFETY DATA SHEET

Product Name: EX-2C TOPCOAT and CLEAR - SFC
Component A

SECTION 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufacturer/Supplier: Endura Manufacturing Co. Ltd.
12425 - 149 Street
Edmonton, Alberta
T5L 2J6
(Ph: (780) 451-4242 Fax: (780) 452-5079)

24-Hour Emergency Number:.... (613) 996-6666 (Canutec)
Product Name:..... EX-2C TOPCOAT and CLEAR - SFC. Component A.
Item Number:..... UN 1263 CI 3 PG II
Chemical Family:..... Ester, Aromatic Hydrocarbon, Ketone, Alkyl Phosphate, Pigments
Material Use:..... 2 Component Flexible Plastic Coating – EX-2C Component "A" must be mixed with an EX-2C Component "B"

SECTION 02: COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	C.A.S.	LD/50, ROUTE, SPECIES	LC/50, ROUTE, SPECIES	TLV	% WT
-----------------------	--------	-----------------------	-----------------------	-----	------

<u>Component A - Polyester Solution</u>					
n-butyl acetate	123-86-4	14 g/kg o-r	2000 ppm/4h i-r	150 ppm	20 – 40
xylene	1330-20-7	4.3 g/kg o-r >2 g/kg d-rbt	5000 ppm/4h i-r	100 ppm	1 – 5
pm acetate	108-65-6	8.5 g/kg o-fr >5 g/kg d-rbt	N/A	N/A	1 – 5
ethyl 3-ethoxypropionate	763-69-9	5 g/kg o-r 10 ml/kg d-rbt	>1000 ppm/6h i-r	N/A	1 – 5
acetone	67-64-1	>9.7 g/kg o-r >20 ml/kg d-rbt	>16000 ppm/4h i-r	500 ppm	1 – 5
dichloro-2-propanol phosphate	13674-87-8	N/A	N/A	N/A	5 – 20

Some colours contain (*) these colours may be reformulated with no lead content when required.

chromium hydroxide	1308-14-1	N/A	N/A	.05 mg/m ₃	0 – 1
lead chromate (*)	7758-97-6	12000 mg/kg o-r	N/A	.05 ppm	0 – 50
lead sulphate (*)	7446-14-2	2000 mg/kg o-r	N/A	.15 ppm	0 – 15
molybdenum compounds n.o.s. (*)	-	N/A	N/A	N/A	0 – 5
mica	12001-26-2	N/A	N/A	3 mg/m ₃	0 – 15
aluminum flake	7429-90-5	N/A	N/A	10 mg/m ₃	0 – 15
carbon black	1333-86-4	>15.4 g/kg o-r >3 g/kg d-rbt	N/A	3.5 mg/m ₃	0 – 5
tin oxide	18282-10-5	>20000 mg/kg o-r	N/A	2 mg/m ₃	0 – 1
ferric oxide	1309-37-1	>5000 mg/kg o-r	N/A	10 mg/m ₃	0 – 50
antimony trioxide	1309-64-4	N/A	N/A	N/A	0 – 5
titanium dioxide	13463-67-7	>25 g/kg o-r >10 g/kg d-rbt	>6.82 mg/l/4h	10 mg/m ₃ /8h	0 – 60
titanium dioxide	1317-80-2	N/A	N/A	10 mg/m ₃	0 – 10
aromatic solvent	64742-95-6	>5 g/kg o-r >3160 mg/kg d-rbt	N/A	N/A	0 – 2
stoddard solvent	8052-41-3	>5 g/kg o-r >3160 mg/kg d-rbt	N/A	100 ppm	0 – 2
dichloro dimethyl silane	68611-44-9	>5000 mg/kg o-r	N/A	10 mg/m ₃	0 – 1
silica-amorphous, precip.	112926-00-8	>10000 mg/kg o-r	N/A	10 mg/m ₃	0 – 15

legend: o=oral r=rat d=dermal i=inhalation rbt=rabbit fr=female rat p=intraperitoneal

See Sax, N.I. "Dangerous Properties of Industrial Materials" for more information.

SECTION 03: HAZARDS IDENTIFICATION

Eye Contact:.... Moderately irritating to eyes and can cause tissue damage.

Skin Contact:... Low toxicity by skin absorption, but extended contact can cause irritation and dermatitis. Skin sensitization or reddening, swelling or blistering can occur.

Inhalation:..... Vapors are of low to moderate toxicity when inhaled and are irritating to nose, throat and other respiratory passages, especially in higher concentrations. Extended exposure can cause headaches, dizziness, nausea or even loss of muscular control and coordination, narcosis or unconsciousness.

Ingestion:..... Liquid is of low to moderate toxicity when ingested, but can be hazardous if aspirated into lungs during swallowing or vomiting.

Additional Information:..... Chronic hazards include narcosis, specific organ damage, permanent brain and nervous system damage or coma if extensively abused. Lead chromate and carbon black are possible carcinogens.

MATERIAL SAFETY DATA SHEET**Product Name:**EX-2C TOPCOAT and CLEAR - SFC
Component A**SECTION 04: FIRST AID MEASURES**

Inhalation (acute):..... Remove to fresh air and restore breathing if necessary by giving artificial respiration. Administer oxygen if victim is breathing with difficulty. GET IMMEDIATE MEDICAL HELP.

Ingestion:..... DO NOT INDUCE VOMITING. Seek medical help. Give 1 or 2 glasses water or milk, BUT ONLY IF VICTIM IS CONSCIOUS.

Eye Contact:..... Check for and remove any contact lenses. Flush eyes IMMEDIATELY with water for 15 minutes and get immediate medical help.

Skin Contact:..... Wash with soap and water. Clean contaminated clothing before reuse.

Notes to Physician:..... Treatment is symptomatic. There is no specific antidote. See list of ingredients.

SECTION 05: FIRE FIGHTING MEASURES

Flash Point (°C), (TCC):..... -18

Auto Ignition Temperature (°C):..... N/A

Upper Explosive Limit (% Vol):... N/A

Lower Explosive Limit (% Vol):..... N/A

Extinguishing Media:..... CO2, dry chemical, foam. Avoid using water except as a fog.

Hazardous Combustion Products:..... CO, CO2. Possibly Oxides of Nitrogen, Sulphur, Lead, Chromium, Antimony or Aluminum.

Sensitivity To Mechanical Impact:..... None

Sensitivity To Static Discharge:..... Can ignite vapors

Special Fire Fighting Procedures:..... Wear self-contained breathing apparatus and full protective clothing. Extreme heat may cause pressure build-up in containers and possibly explosion, therefore use water to keep containers cool.

Conditions of Flammability:..... Sparks, open flame, static discharge or extreme temperature.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak / Spill and Clean up:..... Remove all sources of ignition. The product should be contained and absorbed with inert materials and placed into a container. Do not seal the containers until any gas, which might form, has done so.

SECTION 07: HANDLING AND STORAGE

Handling Procedures:..... Avoid static charges, sparks, flames and excessive heat. Keep containers tightly closed and upright when not in use. Transfer equipment should be properly grounded or bonded. Electrical and mechanical equipment should be explosion-proof. Do not allow contact with skin or eyes and don't breathe vapors.

Storage Needs:..... Store in a cool, dry place.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**PROTECTIVE EQUIPMENT**

Eye/Type:..... Personnel should wear liquid chemical goggles or a full-face shield.

Respiratory/Type:..... Personnel should wear a suitable air supplied respirator.

Gloves/Clothing/Footwear/Type: Personnel should wear chemical-resistant clothing and rubber or plastic (PVA) gloves and boots.

Other/Type:..... A safety shower and eye wash facility should be available.

Ventilation Requirements..... Adequate ventilation must be assured to prevent the accumulation of dangerous amounts of vapor or mist.

MATERIAL SAFETY DATA SHEET**Product Name:** EX-2C TOPCOAT and CLEAR - SFC
Component A**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Physical State (appearance):...	Coloured or clear liquid
Odor:.....	Solvent like
Density (g/ml):.....	1 - 1.6
Odor Threshold (ppm):.....	N/A
Vapor Pressure (@20°C):.....	180 mm Hg
Vapor Density (Air=1):.....	Heavier than air
Evaporation Rate:.....	5.7
Boiling Point (°C):.....	57
pH:.....	N/A
Solubility in Water (% W/W):...	N/A
Coefficient of Water/Oil Distribution:	N/A
Freezing Point (°C):.....	N/A
Melting Point (°C):.....	N/A
VOC:.....	Please refer to each product MSDS

SECTION 10: STABILITY AND REACTIVITY

Reactivity Conditions..... Will react with oxidizing materials.

SECTION 11: REGULATORY INFORMATION

WHMIS Classification:..... B-2, D-2A, D-2B

SECTION 12: DISPOSAL CONSIDERATIONS

Waste Disposal:..... Dispose of waste according to local, provincial and federal regulations. Utilize authorized centers for disposal of combustible chemical material.

SECTION 13: TRANSPORT INFORMATION

T.D.G. Classification:..... Shipping name: Paint related material. UN 1263, CI 3, PG II.

SECTION 14: OTHER INFORMATIONNote:.....
Prepared By:..... Endura – Information Systems
Revision Date:..... January 29, 2009