



• **PRODUCT NAME** **ECO-GRIP® SLIP RESISTANT SAFETY FLOORING**

1. MANUFACTURING Allied Industries International, Inc. 1088 Old Gaffney Hwy, Jonesville, SC 29353
 Phone: (864) 674-0018 Fax: (864) 674-0019

2. PRODUCT DESCRIPTION Eco-Grip® Slip Resistant Safety Flooring is 1/4" thick recycled poly vinyl chloride material flooring designed for slip resistance. Eco-Grip® Slip Resistant Safety Flooring provides superior shock absorbency and is capable of withstanding high impact. The unique surface design provides excellent traction even when wet and/or greasy. Specifically designed not to shrink or harden when exposed to animal fats or caustic chemicals.

3. APPLICATIONS Ideal for commercial kitchens, walk-in coolers, medical facilities, veterinary clinics, locker rooms, weight rooms, gym floors, laboratories, entrance ways, factory and plant floors, multipurpose floors, and as a temporary gym floor protection. Eco-Grip® Slip Resistant Safety Flooring may be installed anywhere that a durable wear layer is required such as commercial kitchens, gym floors, restrooms, hallways, etc.

4. SPECIFICATIONS Size Sheets - 60" x 96" Thickness: 1/4" Surface Finish: Aggressive, textured surface for superior slip resistance. Colors:



Eco-Grip® Slip Resistant Safety Flooring is manufactured from 98% recycled polyvinyl chloride with fabric strand reinforcement to increase overall product flexibility and physical strength.

5. CLEANING INSTRUCTIONS May be cleaned using standard commercial floor cleaning practices. For ease of maintenance, **Eco-Grip® Commercial Kitchen Floor Cleaner** is the recommended concentrate for commercial kitchen applications.

6. INSTALLATION Where to install: Eco-Grip® Slip Resistant Safety Flooring may be installed on most types of clean, dry, level and hard substrates. Eco-Grip® Safety Flooring may be used for both interior and exterior applications.

Surface preparation: Surface should be clean and free of debris that may prohibit Eco-Grip® Slip Resistant Safety Flooring from laying flat. Uneven joints and cracks which create an unlevel condition, should be repaired using an approved underlayment or leveling compound. Eco-Grip® Slip Resistant Safety flooring is to be installed following normal installation procedures. Cutting and trimming can be achieved using a standard utility knife or similar razorblade-type tool.

7. ALLIED INDUSTRIES TEST DATA

Tensile Strength: 1600 psi	Bacteria & Mildew Resistance: Excellent ASTM G-21
Compressive Strength Elongation: 185%	Coefficient of Friction (avg): ASTM D-1894-08 Dry 1.31 Wet 1.07
Hardness: instant /15 seconds 90 - 85 Average	Fire Test: NFPA Type I Rated
Weight (oz. sq. ft.): 25.16 ASTM D-751	Thickness: .250 inches
	Oxygen Index: 29.0

This list is a sampling materials ALLIED INDUSTRIES has seen in the commercial food service environment. Eco-Grip® Slip Resistant Safety Flooring is resistant to these and many more chemicals and ALLIED INDUSTRIES will evaluate any chemical not listed which may be present in a particular application. Data based on ASTM D-543.

Ammonium Chloride	Calcium Chloride	Fluburic Acid	Mineral Spirits
Ammonium Hydroxide	Calcium Hydroxide	Formaldehyde	Motor Oil
Ammonium Nitrate	Calcium Hypochlorite	Gasoline	Muriatic Acid
Ammonium Sulfate	Chicken Fat	Glyoxal	Phosphoric Acid
Amyl Acetate	Chromic Acid	Hexane	Phthalic Acid
Aniline	Citric Acid	Hydrogen Peroxide	Salt Water
Beef Fat	Cutting Oil	Jet Fuel/Diesel Fuel	Sewer Sludge
Benzoic Acid	Detergent Solution	Kerosene	Sodium Hydroxide
	Diethyl Phthalate		Bleach
Boric Acid	Dilute Sodium Hydroxide	Lacquer Spray Paint	Tannic Acid
Butyl Acetate	Ethyl Alcohol	Latex Paint	Triacetin
Butyric Acid	Fertilizer Solution	Malic Acid	Varasol
		Methyl Alcohol	Vegetable Oil