



THE ULTIMATE FLOORING SOLUTION



# CHALLENGING THE NORM

OVERNIGHT INSTALL







DECADE-LONG GUARANTEE



SMILE-WORTHY PRICE TAG



TRUSTED BY SOME OF THE TOP  
BRANDS IN THE BUSINESS



THE FRENCH LAUNDRY



FIVE GUYS  
BURGERS and FRIES

WESTMINSTER

Life Care  
Services



Palm  
RESTAURANT

FOUR SEASONS  
Hotels and Resorts





## A FLOORING SOLUTION GUARANTEED TO LAST

### THE MOST DURABLE SPECIALTY COMMERCIAL FLOORING ON THE MARKET.

**With the chemistry to back it up.**

After years of research and extensive testing, Eco-Grip® has engineered a state-of-the-art flooring formula that is transforming the industry. We combine short staple fiber and unique polyvinyls to create a flooring solution that will not fail.





## FOOD SERVICE



**SLATE**



**PEWTER**




**GRAPHITE**




**CHARCOAL**




**TERRACOTTA**



**MESA**



**MOCHA**



**FOREST**

Commercial kitchens are areas that are continuously exposed to grease, oils, harsh detergents, constant water spills and other harmful chemicals. Eco-Grip **“Safety-Grip”** is specifically designed to ensure safety and durability in these conditions as well as with extreme changes in temperature.

Thickness – 6.5mm • Finish – Aggressive

“It’s watertight, easy to clean, you don’t have to use mats—it’s the perfect product!”

I have it in both my restaurants and never had to replace it. Easy to stand on, easy to clean and my staff loves it!”

**Rob Crenshaw**, Owner, Cabo Fish Taco, Charlotte

“We went with Eco-Grip and I’m sure glad we did. The install was flawless and the floor is holding up very well. I would highly recommend this product and company.”

**Randy Negi**, Danville Brewing

“The product is great, easy on my cook’s feet and easy to clean. It’s much better than poured flooring.”

**Michael Messinger**, Olia Cocina and Farmers Union, San Jose

“Definitely will recommend to all my friends and fellow restaurant owners”

**Amanda Tsung**, Kinjo Sushi, Ijji Sushi and Saru Sushi, San Francisco

“You get what you pay for. We are very satisfied with the outcome. The Santa Clara health department was also impressed with the installation.”

**Jaclyn Nguyen**, Unique Cuisine, San Jose





## VETERINARY



SLATE



PEWTER



GRAPHITE



FOREST




MOCHA

For the challenging environments of pet daycares, equestrian venues and animal hospital facilities Eco-Grip's odor resistant **"Vet-Guard"** with a built-in micro-biocide and easy cleanability is the logical choice.

Thickness – 4mm • Finish – Matte



## MANUFACTURING/INDUSTRIAL



STEEL



SLATE



CHARCOAL


From automotive assembly lines and bottling plants to canning facilities and meat processing factories, Eco-Grip **"Dura-Guard"** 6.5mm heavy duty flooring is designed for the harsh conditions and abuse these facilities exert on flooring.

Thickness – 6.5mm • Finish – Matte





## HEALTHCARE



**STEEL**



**SLATE**



**PEWTER**




**FOREST**

Sanitation, cleanability and comfort under foot are of utmost importance when dealing with healthcare flooring applications. Eco-Grip **“Med-Flex”** is a full 6.5mm thick which provides excellent anti-fatigue qualities and with a built-in micro-biocide, it will prohibit the growth of germs.

Thickness – 6.5mm • Finish – Matte



## ATHLETIC



**MOCHA**



**GRAPHITE**



**CHARCOAL**



**FOREST**

When selecting athletic flooring, overall durability and comfort under foot are key. Eco-Grip **“Sport-Pro”** will exceed the durability of conventional rubber flooring and the slight cushion effect provides a safe and comfortable exercise surface.

Thickness – 6.5mm • Finish – Matte





### OVERNIGHT INSTALL



Avoid loss of revenue with a hassle free installation.

### DECADE-LONG GUARANTEE



Maximize your investment with floors guaranteed to last.

### SMILE-WORTHY PRICE TAG



Competitive pricing for a superior floor.

OUR FLOORS GO THE DISTANCE BECAUSE WE UNDERSTAND THE DAY-TO-DAY IMPACT ON COMMERCIAL FLOORING.

### SLIP-RESISTANT



The most slip resistant safety flooring in the industry... even when wet!

### RESPONSIBLY MADE



Made from 98% recycled content, keeping polyvinyls out of our nation's landfills.

### IMPACT RESISTANT



Reinforced with random short staple PET fiber, Eco-Grip® is both puncture and impact resistant.

### WATERPROOF



Non-porous flooring surface creates a waterproof membrane ideal for above grade installation.

### BOOST MORALE



Flexible, anti-fatigue flooring protects your employees' feet, legs, and lower back, while keeping noise levels in the kitchen to a minimum.

### BACTERIA & CHEMICAL RESISTANT



Advanced chemistry withstands harsh chemicals and animal fats while a built-in micro-biocide prohibits odor causing mold and mildew.





## PRODUCT NAME

### ECO-GRIP® SLIP RESISTANT SAFETY FLOORING

## MANUFACTURING

Allied Industries International, Inc.  
1088 Old Gaffney Hwy, Jonesville, SC 29353  
Phone: (864) 674-0018 Fax: (864) 674-0019

## PRODUCT DESCRIPTION

Eco-Grip® flooring is manufactured from 98% recycled polyvinyl with short staple fiber reinforcement to increase overall product flexibility and physical strength. Eco-Grip® flooring provides superior shock absorbency and is capable of withstanding high impact. The unique surface design provides excellent traction even when wet and/or greasy. Specifically designed not to shrink or harden when exposed to animal fats or caustic chemicals.

## APPLICATIONS

Ideal for commercial kitchens, walk-in coolers, operating rooms, veterinary clinics, locker rooms, weight rooms, gym floors, laboratories, entrance ways, factory and plant floors, multipurpose floors, and as a temporary gym floor protection. Eco-Grip® flooring may be installed anywhere that a durable wear layer is required.

## SPECIFICATIONS

Size Sheets: 60" x 96" Standard  
Thickness: 6.5mm / 4mm  
Weight (oz. sq. ft.): 25.16 / 16  
Surface Finishes: Aggressive food service finish, Smooth matte finish  
Colors: Slate, Pewter, Graphite, Charcoal, Terracotta, Mesa, Mocha, Forest, Steel

## CLEANING INSTRUCTIONS

Each installation includes a cleaning kit (foam gun, degreaser, deck brush & squeegee). Step 1. Remove all loose debris Step. 2. Pre-Rinse the floor with HOT water using your Hot water hose. Step 3. Connect the foam gun directly to the gallon of degreaser and apply a liberal amount on the floor. Step 4. Use the deck brush to agitate the floor. Step 5. Allow the degreaser to dwell for 8 minutes. Step 6. Use HOT water to rinse the floor and the squeegee can be used to direct water towards the floor drains. Refer to the Allied Industrial cleaning instructions for additional details.

## INSTALLATION

**Where to install:** Eco-Grip® flooring may be installed on most types of clean, dry, level and hard substrates. Eco-Grip® flooring may be used for both interior and exterior applications.

**Surface preparation:** Surface should be clean and free of debris that may prohibit Eco-Grip® flooring from laying flat. Uneven joints and cracks which create an unlevel condition, should be repaired using an approved underlayment or leveling compound. Eco-Grip® flooring is to be installed following normal installation procedures. Cutting and trimming can be achieved using a standard utility knife or similar razorblade-type tool. Please refer to the Allied Industries Installation Manual for additional details.

## ALLIED INDUSTRIES TEST DATA

Bacteria & Mildew Resistance: Excellent ASTM G-21  
Tensile Strength: 1600 psi  
ASTM F920: 2000 psi  
ANSI B101.1 SCOF = .62 DCOF = .43  
Compressive Strength Elongation: 185%  
ASTM 662 DMC = 141  
Fire Test: NFPA Type I Rated  
Hardness: instant /15 seconds 90 - 85 Average  
Thickness: 6.5mm / 4mm  
Weight (oz. sq. ft.): 25.16 / 16  
Oxygen Index: 29.0

Eco-Grip® flooring is resistant to these and many more chemicals and ALLIED INDUSTRIES will evaluate any chemical not listed which may be present in a particular application. Data based on ASTM D-543.

Eco-Grip® flooring is extremely resistant to the chemical compounds listed: Ammonium Chloride, Calcium Chloride, Fluburic Acid, Mineral Spirits, Ammonium Hydroxide. Calcium Hydroxide. Formaldehyde. Motor Oil, Ammonium Nitrate, Calcium Hypochlorite, Gasoline, Muriatic Acid, Ammonium Sulfate, Chicken Fat, Glyoxal, Phosphoric Acid, Amyl Acetate, Chromic Acid, Hexane, Phthalic Acid, Aniline, Citric Acid, Hydrogen Peroxide, Salt Water, Beef Fat, Cutting Oil, Jet Fuel/Diesel Fuel, Sewer Sludge, Benzoic Acid, Detergent Solution, Kerosene, Sodium Hydroxide, Bleach, Diethyl Phthalate, Lacquer Spray Paint, Tannic Acid, Boric Acid, Dilute Sodium Hydroxide, Latex Paint, Triacetin, Butyl Acetate, Ethyl Alcohol, Malic Acid, Varasol, Butyric Acid, Fertilizer Solution, Methyl Alcohol, Vegetable Oil



800-767-5754 Toll Free

**Manufacturing/  
International Distribution**  
1088 Gaffney Hwy  
Jonesville, SC 29353  
864-674-0018 ph  
864-674-0019 fax

**National Training Center/  
SpeedFlex Production**  
3013 Bank Street  
Charlotte, NC 28203  
704-522-0597 ph  
704-522-0598 fax

800-767-5754 Toll Free  
sales@eco-gripfloor.com  
customerservice@eco-gripfloor.com  
www.eco-gripfloor.com

