



PRODUCT NAME

ECO-GRIP® SLIP RESISTANT SAFETY FLOORING

MANUFACTURING

Allied Industries International, Inc.
1088 Gaffney Hwy, Jonesville, SC 29353
Phone: (864) 674-0018 Fax: (864) 674-0019

PRODUCT DESCRIPTION

Eco-Grip® flooring is manufactured from 98% recycled polyvinyl with short staple fiber reinforcement to increase overall product flexibility and physical strength. Eco-Grip® provides superior shock absorbency and is impact resistant. The unique surface design produces excellent traction even when wet and/or greasy, and the “walk-in” feature provides increased slip resistance over prolonged use. Specifically designed not to shrink or harden when exposed to animal fats or caustic chemicals, Eco-Grip® is manufactured using polymeric plasticizers and is designed to remain stable through extreme temperature changes.

APPLICATIONS

Ideal for areas requiring a durable, waterproof, easy-to-clean floor system, including: commercial kitchens, walk-in coolers, freezer, food prep areas, dish areas, commissary food service, mobile kitchens, and bulk food production facilities. Eco-Grip® can also be installed as a highly durable sanitary wall treatment, protecting walls from carts, bins, and water overspray.

SPECIFICATIONS

Size Sheets: 60” x 96”
Thickness: 6.5mm
Weight (oz. sq. ft): 25.16
Wear layer: 6mm
Surface Finish: Aggressive slip resistant finish
Solid Colors: Slate, Pewter, Charcoal, Forest, Mocha, Mesa

CLEANING INSTRUCTIONS

Each installation includes a cleaning kit (hot water hose, foam gun, degreaser, deck brush & squeegee). Step 1. Remove all loose debris. Step 2. Pre-Rinse the floor with HOT water using your hot water hose. Step 3. Fill the foam gun reservoir with Eco-Grip® degreaser and apply a liberal amount on the floor. Step 4. Use the deck brush to scrub the floor as needed. Step 5. Allow the degreaser to dwell on the floor for 8 minutes. Step 6. Use HOT water to rinse the floor and the squeegee can be used to direct water toward the floor drains. Refer to the Eco-Grip® Floor Cleaning Manual for additional details.

INSTALLATION

Eco-Grip® flooring may be installed on most clean, dry, level and hard substrates. Eco-Grip® may be used for both interior and exterior applications.

Surface Preparation: Surface should be clean and free of debris and registering no more than 98% relative humidity. Eco-Grip® should lay flat and uneven joints and cracks in the substrate should be repaired using an approved underlayment or leveling compound. Eco-Grip® is to be installed following standard Allied installation procedures. Cutting and trimming can be achieved using a hook blade razor tool. Please refer to the Allied Industries Installation Manual for additional details.

ALLIED INDUSTRIES TEST DATA

ASTM G21: Excellent Bacteria & Mildew Resistance
ASTM D412 Tensile Strength: 1694 psi Elongation 130.98%
ASTM D624 Tear Strength: 268 lbs/force/inch Elongation 27.33%
ASTM F970 2000 psi .023 Avg 1500 psi = .014
ANSI B101.3 SCOF = .62 DCOF = .43
ANSI B101.3 DCOF TRL rubber = .72
ASHB 198:2014 SSR Wet = 65
ASTM E662 Smoke Density: DMC 141
Fire Test: NFPA Type I Rated
ASTM D2240 Hardness: 85
Thickness: 6.5mm
Weight (oz. sq. ft.): 25.16
Oxygen Index: 29.0

Eco-Grip® flooring is resistant to the chemicals listed below and Allied Industries will evaluate any chemical not listed which may be present in a particular application. Data based on ASTM D-543; Acetate, Ammonium Chloride, Ammonium Hydroxide, Ammonium Nitrate, Ammonium Sulfate, Amyl Aniline, Benzoic Acid, Boric Acid, Butyl Acetate, Butyric Acid, Calcium Chloride, Calcium Hydroxide, Calcium Hypochlorite, Chromic Acid, Citric Acid, Cutting Oil, Ethyl Alcohol, Formaldehyde, Glyoxal, Hydrogen Peroxide, Methyl Alcohol, Mineral Spirits, Diethyl Phthalate, Malic Acid, Phosphoric Acid, Sodium Hydroxide, Triacetin, Varasol



Manufacturing/International Distribution
1088 Gaffney Hwy • Jonesville, SC 29353
864-674-0018 ph • 864-674-0019 fax

National Training Center/SpeedFlex Production
3013 Bank Street • Charlotte, NC 28203
704-522-0597 ph • 704-522-0598 fax

sales@eco-gripfloor.com
customerservice@eco-gripfloor.com
www.eco-gripfloor.com



Made in USA



800-767-5754 Toll Free